# **PANZERI**

## Gonio

220-240V AC dimmable (DALI/Push DIM)

A01901.045.0402

## white



#### Data sheet

CODE	A01901.045.0402
SYSTEM POWER CONSUMPTION	35W
EFFICACY	96.51lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B50) 72.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	asymmetric
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	4860lm
LUMEN OUTPUT	3378lm
EFFICIENCY	69.5%
WEIGHT	1,63 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	18,0 x 46,0 x 20,0 cm



Wall lighting fixture for interiors, with direct and indirect light emission.

Pickled sheet metal wall bracket in polyacrylic paint.

 ${\sf Extruded\ aluminium\ structure\ in\ white,\ black,\ bronze,\ mat\ brass\ or\ titanium\ polyacrylic}$ 

Extruded acrylic diffusers with opaline finish.

Die-cast aluminium end caps in polyacrylic paint.







#### **Technical drawing**



### Polar diagram

