

## Gonio

220-240V AC dimmable (DALI/Push DIM)  
A01901.060.0402

white




### Data sheet

CODE	A01901.060.0402
SYSTEM POWER CONSUMPTION	45W
EFFICACY	100.07lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B50) 72.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	asymmetric
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	6480lm
LUMEN OUTPUT	4503lm
EFFICIENCY	69.5%
WEIGHT	2,05 Kg
PROTECTION DEGREE	IP40
COLOUR TOLERANCES	SDCM 3
PACKING DIMENSIONS	12,5 x 63,0 x 14,0 cm



### Technical drawing



Wall lighting fixture for interiors, with direct and indirect light emission.  
Pickled sheet metal wall bracket in polyacrylic paint.  
Extruded aluminium structure in white, black, bronze, mat brass or titanium polyacrylic paint.  
Extruded acrylic diffusers with opaline finish.  
Die-cast aluminium end caps in polyacrylic paint.

### Polar diagram

