PANZERI

Gonio

220-240V AC dimmable (DALI/Push DIM)
A01901.060.0502

white

DIRECT + INDIRECT LIGHT

Data sheet

CODE	A01901.060.0502
SYSTEM POWER CONSUMPTION	45W
EFFICACY	96.38lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B50) 72.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	asymmetric
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	6240lm
LUMEN OUTPUT	4337lm
EFFICIENCY	69.5%
WEIGHT	2,05 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	12,5 x 63,0 x 12,5 cm



Wall lighting fixture for interiors, with direct and indirect light emission.
Pickled sheet metal wall bracket in polyacrylic paint.
Extruded aluminium structure in white, black, bronze, mat brass or titanium polyacrylic paint.
Extruded acrylic diffusers with opaline finish.
Die-cast aluminium end caps in polyacrylic paint.

Technical drawing



Polar diagram

