PANZERI

Gonio

220-240V AC dimmable (DALI/Push DIM)

A01902.030.0402





Data sheet

CODE	A01902.030.0402
SYSTEM POWER CONSUMPTION	24W
EFFICACY	93.83lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B50) 72.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	asymmetric
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	3240lm
LUMEN OUTPUT	2252lm
EFFICIENCY	69.5%
WEIGHT	1,08 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	19,5 x 35,0 x 10,0 cm



Wall lighting fixture for interiors, with direct and indirect light emission.

Pickled sheet metal wall bracket in polyacrylic paint.

 ${\sf Extruded\ aluminium\ structure\ in\ white,\ black,\ bronze,\ mat\ brass\ or\ titanium\ polyacrylic}$

Extruded acrylic diffusers with opaline finish.

Die-cast aluminium end caps in polyacrylic paint.







Technical drawing



Polar diagram

