

PANZERI

Gonio

220-240V AC dimmable (DALI/Push DIM)

A01902.030.0402



Data sheet


CODE	A01902.030.0402
SYSTEM POWER CONSUMPTION	24W
EFFICACY	93.83lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B50) 72.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	asymmetric
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	3240lm
LUMEN OUTPUT	2252lm
EFFICIENCY	69.5%
WEIGHT	1,08 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	19,5 x 35,0 x 10,0 cm



Wall lighting fixture for interiors, with direct and indirect light emission.
Pickled sheet metal wall bracket in polyacrylic paint.
Extruded aluminium structure in white, black, bronze, mat brass or titanium polyacrylic paint.
Extruded acrylic diffusers with opaline finish.
Die-cast aluminium end caps in polyacrylic paint.



Technical drawing



Polar diagram

