# **PANZERI**

# Zero Line

220-240V AC ON-OFF

A03601.050.0501





#### Data sheet

CODE	A03601.050.0501
SYSTEM POWER CONSUMPTION	12,2W
EFFICACY	53.33lm/W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	ON-OFF
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	1448lm
LUMEN OUTPUT	640lm
EFFICIENCY	44.2%
WEIGHT	0,92 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	10,0 x 83,0 x 5,0 cm



Ceiling or wall lighting fixture for interiors, with direct and indirect light emission. gold leaf coating, or in polished stainless steel.

Specular aluminium reflector.

Cover in brass with white, bronze or mat brass polyacrylic paint, or with gold leaf coating, or with galvanic chrome plating.


Extruded polycarbonate diffuser with opaline finish.







## Technical drawing



## **Application**

