

PANZERI

Zero Line

220-240V AC ON-OFF
A03622.100.0501



Data sheet

| | |
|--------------------------|-----------------------|
| CODE | A03622.100.0501 |
| SYSTEM POWER CONSUMPTION | 22,2W |
| EFFICACY | 71.45lm/W |
| LIGHT SOURCE | LED |
| COLOUR TEMPERATURE | 2700K Ra>90 |
| LIGHT DISTRIBUTION | diffused |
| POWER SUPPLY | 220-240V AC |
| FREQUENCY | 50/60Hz |
| ELECTRICAL CONFIGURATION | ON-OFF |
| DRIVER | integrated included |
| NOMINAL LUMINOUS FLUX | 2896lm |
| LUMEN OUTPUT | 1572lm |
| EFFICIENCY | 54.3% |
| WEIGHT | 1,58 Kg |
| PROTECTION DEGREE | IP20 |
| COLOUR TOLLERANCES | SDCM 3 |
| PACKING DIMENSIONS | 10,0 x 105,0 x 5,0 cm |



Ceiling or wall lighting fixture for interiors, with direct and indirect light emission. Pickled sheet metal structure in white, bronze or mat brass polyacrylic paint, or with gold leaf coating, or in polished stainless steel. Specular aluminium reflector. Cover in brass with white, bronze or mat brass polyacrylic paint, or with gold leaf coating, or with galvanic chrome plating. Extruded polycarbonate diffuser with opaline finish.

Technical drawing

Application

