


## Bella

220-240V AC dimmable (Step DIM)

A05217.011.0509



### Data sheet

CODE	A05217.011.0509
SYSTEM POWER CONSUMPTION	5W
EFFICACY	77.6lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B10) 70.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	adjustable
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (Step DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	460lm
LUMEN OUTPUT	388lm
EFFICIENCY	84.3%
WEIGHT	0.56 Kg
PROTECTION DEGREE	IP20
COLOUR TOLERANCES	SDCM 3
PACKING DIMENSIONS	12,0 x 24,0 x 13,0 cm



Ceiling or wall lighting fixture for interiors, with swivelling light beam.  
Galvanized sheet metal ceiling or wall bracket.

Die-cast aluminium wall plate in white, black, bronze, mat brass or titanium polyacrylic paint.

Turned brass joints in polyacrylic paint.

Die-cast aluminium structure in polyacrylic paint.



Die-cast aluminium head rotating on three axes in polyacrylic paint.

Modelled acrylic diffuser with mat finish.

Aluminium closing disk in polyacrylic paint.

Push-button to adjust luminosity according to 5 levels of visual comfort.

### Technical drawing



### Application

