# **PANZERI**

## Dip

#### 220-240V AC dimmable (DALI/Push DIM)

A08428.070.0502





#### Data sheet

CODE	A08428.070.0502
SYSTEM POWER CONSUMPTION	18W
EFFICACY	107.28lm/W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	3013lm
LUMEN OUTPUT	1931lm
EFFICIENCY	64.1%
WEIGHT	2,64 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	49,0 x 119,0 x 19,0 cm



Wall installation lighting fixture for interiors, with direct or indirect light emission. Power supply canopy with pickled sheet metal fixing bracket, deep-drawn sheet metal  $% \left( 1\right) =\left( 1\right) \left( 1\right) +\left( 1\right) \left( 1\right) \left( 1\right) +\left( 1\right) \left( 1\right) \left($ closing frame in polyacrylic paint.

Calendered steel tube stem, with polyacrylic paint.

Die-cast aluminum emitting head with polyacrylic paint in champagne, mat black, bronze and soft textured white finishes.


 ${\tt UV}\ technology\ screen-printed\ diffuser,\ made\ of\ opal\ polycarbonate,\ installed\ with$ magnetic coupling.








#### Technical drawing



### Polar diagram



<u>cd/klm</u> C0 - C180 - - - C90 - C270

# **PANZERI**

# Dip

## Accessories / diffusion

YKG08428.01

Anti-glare grid kit for Dip (indoor)



