PANZERI

Jay

220-240V AC ON-OFF

A13517.033.0501





Data sheet

CODE	A13517.033.0501
SYSTEM POWER CONSUMPTION	18W
EFFICACY	44.28lm/W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused + adjustable
BEAM ANGLE	34°
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	ON-OFF
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	1180lm
LUMEN OUTPUT	797lm
EFFICIENCY	67.5%
WEIGHT	1,25 Kg
PROTECTION DEGREE	IP20
PACKING DIMENSIONS	16,0 x 39,0 x 16,0 cm









Wall lighting fixture for interiors, with indirect light emission and swivelling accent light. Aluminium wall bracket with shelf for installation on the left side of the bed, in white,

black, bronze, mat brass or titanium polyacrylic paint.

Pickled sheet metal structure in polyacrylic paint.

Extruded aluminium heat sink.

Extruded polycarbonate diffuser with opaline finish.

Die-cast aluminium joint with polyacrylic paint.

Die-cast aluminium projector rotating on two axes in polyacrylic paint.

 $\label{lem:reflector} \textit{Reflector} \ \textit{in} \ \textit{thermoplastic} \ \textit{material} \ \textit{with} \ \textit{chrome} \ \textit{plated} \ \textit{finish}.$

Textured glass screen.

Anti-glare snoot in black thermoplastic material.

Double power switch for indirect light only, reading light only or combined.

Equipped with USB socket for charging batteries of electronic devices.

Technical drawing



