PANZERI

Zero Round

220-240V AC ON-OFF A15330.025.0501

Data sheet

CODE	A15330.025.0501
SYSTEM POWER CONSUMPTION	11,5W
EFFICACY	90.91lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B50) 60.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	ON-OFF
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	1100lm
LUMEN OUTPUT	1000lm
EFFICIENCY	90.9%
WEIGHT	0,62 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	31,0 x 31,0 x 20,0 cm



Wall lighting fixture for interiors, with direct and indirect light emission. Pickled sheet metal wall bracket in polyacrylic paint. Pickled sheet metal wall plate in polyacrylic paint. Bended extruded aluminium structure in white, black, bronze, mat brass or titanium polyacrylic paint.


Extruded polycarbonate diffuser with opaline finish.

CE ERE 🗵

Technical drawing

Polar diagram

titanium



<u>cd/klm</u> _____C0 - C180 _ - - - C90 - C270