Astoria Spot

48V DC dimmable (DALI)





Data sheet

CODE	B43002.030.1719
SYSTEM POWER CONSUMPTION	5,7W
EFFICACY	82.8lm/W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	flood
BEAM ANGLE	30°
POWER SUPPLY	48V DC
ELECTRICAL CONFIGURATION	dimmable (DALI)
DRIVER	remote not included
LUMEN OUTPUT	414lm
WEIGHT	0,22 Kg
PROTECTION DEGREE	IP20
PACKING DIMENSIONS	0,0 x 0,0 x 0,0 cm





Linear LED module for 48V low voltage electrified track, for ceiling/wall, suspensed or recessed applications, available in two different lenghts.

Black aluminium body, 30° beam polycarbonate lens and plastic cover.

Available in 2700K and 3000K.

Possibility of dimming with DALI protocol.










Technical drawing








Application



Polar diagram



Astoria Spot

Accessories / electrified tracks

9500-2/B-ST2-E

C € [HI 🗵 🐵

Suspensed or ceiling-mounted 48V DC DALI electrified track, 2000mm (78,7") long.



9500-2/B-ST5-E

Recessed 48V DC DALI electrified track, 2000mm (78,7") long.







Astoria Spot

Accessories / electrified tracks / power supply

9500/P-100E-B-C1-N

CE EHI 🗵 瞰

Power supply kit with canopy for ceiling-mounted electrified track, with 100W/48V driver and power supply head with 200mm (7.87") long cable.



9500/P-100E-B-SP-N

CE EHI 🗵 🎰

CE [HI 🗵 🐽

Power supply kit with canopy for electrified suspensed track, with 100W/48V driver and power supply head with 2000mm (78,7") long cable.



YBE41002.DV1

Integrated 100W power supply for electrified 48V DALI track.



YDV.048.075.A01

CE EHI 🗵 瞰

LED driver, 75W 48V DC, on/off.



YDV.048.150.A01

LED driver, 150W 48V DC, on/off.











Astoria Spot

Accessories / electrified tracks / power supply and closing

9501-S/B-E

Head power supply for 48V DC DALI electrified track.









Astoria Spot

CE EHI 🗵 🐽

Accessories / electrified tracks / closing

9504/ST2-B

End cap for 48V DC electrified track, without power supply hole.

9504/ST2-B-F

End cap for 48V DC electrified track, with power supply hole.

CE HIL

O

Protective cover for recessed electrified track installation. Length 2000mm (78.7").

S-9500/LE-B-3000

Aesthetic cover for 48V DC electrified track, length 3000mm (118.1").

Astoria Spot

Accessories / electrified tracks / fixing

9500-KIT1-3

End suspension kit, with 3000mm (118.1") long steel wire, for electrified track.









S-9000-P4

Suspension kit with rigid tige 1000mm (39,4") long for recessed track.









S-9000/118

Clip for quick fastening with turnbuckle for rigid suspension tige.














S-9500/114-B

Ceiling mounting kit for 48V DC electrified track.











Astoria Spot

Accessories / electrified tracks / junction

9503-S/B-E


CE EHI 🗵 🐵

Linear electrified joint for 48V DC DALI track.



9511/B-E

Electrified "L" joint for 48V DC DALI track.









9518-S/B-E

Flexible electrified joint for 48V DC DALI track.













S-9500/314-B

Linear mechanical junction for recessed electrified 48V DC track.











S-9500/323-SV

Linear junction for suspensed or ceiling-mounted electrified track.













S-9511-I/B-ST5

Internal wall/ceiling "L" joint for 48V DC recessed trimless electrified track.













S-9511/B-ST2

"L" junction for 48V DC suspensed or ceiling-mounted electrified track.











S-9511/B-ST5

Mechanical "L" joint for 48V DC recessed trimless electrified track.











Astoria Spot

Accessories / electrified tracks / fixing and junction

9500-KIT2-3

Fixing and junction kit, with 3000mm (118.1") long steel wire, for suspended electrified track.





Astoria Spot

Accessories / binari elettrificati / signal control

YRS.B048.A16

C € [HI 🗵 🕸

Repeater device for opto-isolating the data bus, for 48V DC DALI electrified track.

