### Queens 45

220-240V AC ON-OFF B77001.037.4001

#### Data sheet

CODE	B77001.037.4001
SYSTEM POWER CONSUMPTION	37W
EFFICACY	120.27lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B10) 50.000h
COLOUR TEMPERATURE	3000K Ra>85
LIGHT DISTRIBUTION	adjustable
BEAM ANGLE	30°
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	ON-OFF
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	5000lm
LUMEN OUTPUT	4450lm
EFFICIENCY	89%
WEIGHT	1,00 Kg
PROTECTION DEGREE	IP20
GLOW WIRE TEST PERFORMANCE	850°
PACKING DIMENSIONS	19,0 x 29,0 x 14,0 cm




Lighting fixture for electrified track for interiors, with swiveling light beam. Die-cast aluminium joint with powder paint. Die-cast aluminium structure rotating on two axes in white or black powder paint. Reflector in thermoplastic material with chrome plated finish. Anti-glare snoot in black thermoplastic material.

Equipped with electric and mechanical adapter for three-phase electrified tracks.

# CEERI 🗵 🗆

#### Technical drawing




#### Application

white



#### Polar diagram



cd/klm \_\_\_\_\_\_C0 - C180 - - - C90 - C270

### Queens 45

Accessories / diffusion

XMR1


Narrow beam optic.

CE ERE 🗵 🗆

XMR3

Wide flood optic.

CE ERE 🗵 🗆



40 mm

74 mm

m"

## Queens 45

### Accessories / electrified tracks


хм7501-100 С є ЕНІ 🗵 🗖	Three-phase electrified track for suspended or ceiling installation for interiors. Structure in anodized extruded aluminium or with white or black powder paint. Copper conductors housed inside extruded section bars in PVC with high isolation resistance. 230-250V AC line voltage or 380-440V AC industrial line voltage power supply. 16A total electrical load. Fastening, joining and closing accessories to be ordered separately. Length: 1m (39,4")	36 mm 1 3/r Building and a second sec
хм7501-200 С € ЕН X 🔲	Three-phase electrified track for suspended or ceiling installation for interiors. Structure in anodized extruded aluminium or with white or black powder paint. Copper conductors housed inside extruded section bars in PVC with high isolation resistance. 230-250V AC line voltage or 380-440V AC industrial line voltage power supply. 16A total electrical load. Fastening, joining and closing accessories to be ordered separately. Length: 2m (78,7")	38 mm 1 3/2 Burger Provide Arriter
хм7501-300 С € ЕНІ 🗵 🗖	Three-phase electrified track for suspended or ceiling installation for interiors. Structure in anodized extruded aluminium or with white or black powder paint. Copper conductors housed inside extruded section bars in PVC with high isolation resistance. 230-250V AC line voltage or 380-440V AC industrial line voltage power supply. 16A total electrical load. Fastening, joining and closing accessories to be ordered separately. Length: 3m (118,1°)	36 mm 13/7 BUBL BUBL ST

### Queens 45

#### Accessories / electrified tracks / adapters

### XM7501


Electro/mechanical adapter 6A, mechanical load 5kg, for three-phase electrified track.



ectro/mechanical adapter OA, mechanical load Skg, for three-phase electrified tra

XM76B01

CE EAE 🗵 🗆





### Queens 45

#### Accessories / electrified tracks / power supply and closing

XM76ADX01

Right live-end for three-phase electrified track.







Left live-end for three-phase electrified track.








mm 314

80 mm 314,



## Queens 45

### Accessories / electrified tracks / power supply and junction

XM76A01

Central connector and straight joint for three-phase electrified track.





### Queens 45

#### Accessories / electrified tracks / closing





Cover 1000mm (39,4") long for three-phase electrified track.



XM76E01

End cap for three-phase electrified track.



### Queens 45

#### Accessories / electrified tracks / fixing

#### XM76K

Ceiling kit for three-phase electrified track.








XM76S01

CE ERE 🗵 🗆





## Queens 45

### Accessories / electrified tracks / junction

xm76f01 Ceeffic	Flexible joint for three-phase electrified track.	Starting Starting
XM76LE01 C C FAI X D	External "L" joint for three-phase electrified track.	
XM76LI01 Ceffi I	Internal "L" joint for three-phase electrified track.	80 mm 3 3,50m
хм76м01 С € ЕНГ 🗵 🗆	Mobile joint for three-phase electrified track.	240°
xm76q01 Ceeffi	Electrical straight joint with stop for three-phase electrified track.	80 mm 3 /2,
xm76tdx01 Ceeffic a d	Right "T" joint for three-phase electrified track.	130 1707
XM76TSX01	Left "T" joint for three-phase electrified track.	120 mm 4 32:-
хм76∪01 С€ [HI] 🗵 🗆	Mechanical straight joint for three-phase electrified track.	132 132 133 132 132 132 132
XM76X01 Ceeffi X	"X" joint for three-phase electrified track.	120 mm 7 34-