PANZERI

432 Ways Street

48V DC dimmable (DALI)

BP12719.006.0419





Data sheet

CODE	BP12719.006.0419
SYSTEM POWER CONSUMPTION	6,7W
EFFICACY	128.83lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L90 (B10) 50.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
BEAM ANGLE	29°
POWER SUPPLY	48V DC
ELECTRICAL CONFIGURATION	dimmable (DALI)
DRIVER	remote not included
NOMINAL LUMINOUS FLUX	878lm
LUMEN OUTPUT	773lm
EFFICIENCY	88%
WEIGHT	0,00 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	0,0 x 0,0 x 0,0 cm



Ceiling lighting fixture for interiors, with direct light emission. $\label{thm:extruded} \textbf{Extruded} \ \text{and} \ \textbf{milled} \ \textbf{aluminium} \ \textbf{structure,} \ \textbf{with} \ \textbf{polyacrylic} \ \textbf{paint} \ \textbf{finish} \ \textbf{in} \ \textbf{white,} \ \textbf{black,}$ bronze, mat brass, textured olive green or textured natural terracotta.

Lens holder not included, to be purchased separately.


Supplied complete with 48V track adaptor from the Street series.







Technical drawing



Polar diagram