PANZERI

Gilbert

220-240V AC ON-OFF

C06501.022.0401





Data sheet

CODE	C06501.022.0401
SYSTEM POWER CONSUMPTION	11W
EFFICACY	62.91lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B20) 60.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	ON-OFF
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	861lm
LUMEN OUTPUT	692lm
EFFICIENCY	80.4%
WEIGHT	0,74 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	27,0 x 35,0 x 22,0 cm



Table lighting fixture for interiors, with direct and indirect light emission.

Turned pickled sheet metal bearing base in white polyacrylic paint.

Aluminium dissipation plate.

Diffuser in mat white blown glass.


Equipped with a 1,3m (51,2") long power cable in transparent PVC with plug and switch.







Technical drawing



Polar diagram

