PANZERI

Opuntia

220-240V AC DIM-to-warm + tunable white C06801.000.9121

Data sheet

| CODEC06801.000.9121SYSTEM POWER CONSUMPTION8,5WEFFICACY87.5lm/WLIGHT SOURCELEDCOLOUR TEMPERATURE2200-4000K Ra>90LIGHT DISTRIBUTIONadjustablePOWER SUPPLY220-240V ACFREQUENCY50/60HzELECTRICAL CONFIGURATIONDIM-to-warm + tunable whiteDRIVERintegrated includedLUMEN OUTPUT700lmWEIGHT3,45 KgPROTECTION DEGREEIP40PACKING DIMENSIONS19,0 x 107,0 x 6,5 cm | | |
|--|--------------------------|-----------------------------|
| EFFICACY 87.5lm/W LIGHT SOURCE LED COLOUR TEMPERATURE 2200-4000K Ra>90 LIGHT DISTRIBUTION adjustable POWER SUPPLY 220-240V AC FREQUENCY 50/60Hz ELECTRICAL CONFIGURATION DIM-to-warm + tunable white DRIVER integrated included LUMEN OUTPUT 700Im WEIGHT 3,45 Kg PROTECTION DEGREE IP40 | CODE | C06801.000.9121 |
| LIGHT SOURCE LED LIGHT SOURCE LED COLOUR TEMPERATURE 2200-4000K Ra>90 LIGHT DISTRIBUTION adjustable POWER SUPPLY 220-240V AC FREQUENCY 50/60Hz ELECTRICAL CONFIGURATION DIM-to-warm + tunable white DRIVER integrated included LUMEN OUTPUT 700Im WEIGHT 3,45 Kg PROTECTION DEGREE IP40 | SYSTEM POWER CONSUMPTION | 8,5W |
| COLOUR TEMPERATURE 2200-4000K Ra>90 LIGHT DISTRIBUTION adjustable POWER SUPPLY 220-240V AC FREQUENCY 50/60Hz ELECTRICAL CONFIGURATION DIM-to-warm + tunable white DRIVER integrated included LUMEN OUTPUT 700Im WEIGHT 3,45 Kg PROTECTION DEGREE IP40 | EFFICACY | 87.5lm/W |
| LIGHT DISTRIBUTION adjustable POWER SUPPLY 220-240V AC FREQUENCY 50/60Hz ELECTRICAL CONFIGURATION DIM-to-warm + tunable white DRIVER integrated included LUMEN OUTPUT 700Im WEIGHT 3,45 Kg PROTECTION DEGREE IP40 | LIGHT SOURCE | LED |
| POWER SUPPLY 220-240V AC FREQUENCY 50/60Hz ELECTRICAL CONFIGURATION DIM-to-warm + tunable white DRIVER integrated included LUMEN OUTPUT 700lm WEIGHT 3,45 Kg PROTECTION DEGREE IP40 | COLOUR TEMPERATURE | 2200-4000K Ra>90 |
| FREQUENCY 50/60Hz ELECTRICAL CONFIGURATION DIM-to-warm + tunable white DRIVER integrated included LUMEN OUTPUT 700lm WEIGHT 3,45 Kg PROTECTION DEGREE IP40 | LIGHT DISTRIBUTION | adjustable |
| ELECTRICAL CONFIGURATION DIM-to-warm + tunable white DRIVER integrated included LUMEN OUTPUT 700lm WEIGHT 3,45 Kg PROTECTION DEGREE IP40 | POWER SUPPLY | 220-240V AC |
| DRIVER integrated included LUMEN OUTPUT 700lm WEIGHT 3,45 Kg PROTECTION DEGREE IP40 | FREQUENCY | 50/60Hz |
| LUMEN OUTPUT 700lm WEIGHT 3,45 Kg PROTECTION DEGREE IP40 | ELECTRICAL CONFIGURATION | DIM-to-warm + tunable white |
| WEIGHT 3,45 Kg PROTECTION DEGREE IP40 | DRIVER | integrated included |
| PROTECTION DEGREE IP40 | LUMEN OUTPUT | 700lm |
| | WEIGHT | 3,45 Kg |
| PACKING DIMENSIONS 19,0 x 107,0 x 6,5 cm | PROTECTION DEGREE | IP40 |
| | PACKING DIMENSIONS | 19,0 x 107,0 x 6,5 cm |


CEERE 🗵 🗆



Die-cast aluminium head rotating on two axes in polyacrylic paint.

Modelled polycarbonate diffuser with opaline finish and serigraphy. Push-button to adjust luminosity and light shade according to 5 levels of visual comfort. Equipped with a 1,6m (63") long power cable with jack connector and adapter plug.

Technical drawing



Polar diagram

