PANZERI

Jackie

220-240V AC dimmable (Step DIM)

CA07730.000.0409





Data sheet

CODE	CA07730.000.0409
SYSTEM POWER CONSUMPTION	10W
EFFICACY	70.6lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L90 (B10) 50.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	adjustable
BEAM ANGLE	90°
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (Step DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	884lm
LUMEN OUTPUT	706lm
EFFICIENCY	79.9%
WEIGHT	0,84 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	6,0 x 119,0 x 25,0 cm



Wall lighting fixture for interiors, with swivelling light beam.

Pickled sheet metal wall bracket in polyacrylic paint.

Extruded aluminium frame in white, black, red or titanium polyacrylic paint.

Die-cast aluminium joints in polyacrylic paint.

Steel wire rope slings.

 $\label{eq:Die-cast} \mbox{ Die-cast aluminium head rotating on two axes in polyacrylic paint.}$

 $\label{thm:modelled} \mbox{Modelled acrylic diffuser with mat finish and double serigraphy}.$


Push-button to adjust luminosity according to 5 levels of visual comfort. Equipped with a 1,6m (63") long power cable with jack connector and adapter plug.








Technical drawing



Polar diagram



<u>cd/klm</u> C0 - C180 - - - C90 - C270