

Coralys

battery
EC14467.022.6114

clay green




Data sheet

CODE	EC14467.022.6114
SYSTEM POWER CONSUMPTION	2,5W
EFFICACY	100lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B10) 50.000h
COLOUR TEMPERATURE	2700-3000-4000K
LIGHT DISTRIBUTION	diffused
ELECTRICAL CONFIGURATION	battery
NOMINAL LUMINOUS FLUX	300lm
LUMEN OUTPUT	200lm
EFFICIENCY	66.7%
WEIGHT	0,00 Kg
PROTECTION DEGREE	IP54
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	0,0 x 0,0 x 0,0 cm



Portable battery-powered lamp for outdoor environments.
The structure is made of interlocking aluminium ribs and features a die-cast aluminium head with magnetic coupling.
The polycarbonate diffuser screen conceals an LED source that offers the possibility of adjusting both light intensity and colour temperature (2700K-3000K-4000K) by the touch button positioned on the head.
Recharging the device is carried out via a USB-C port located on the diffuser screen.
USB-C charging cable included.

Technical drawing



Polar diagram