PANZERI

Venexia

220-240V AC ON-OFF

EL04816.022.0201





Data sheet

CODE	EL04816.022.0201
SYSTEM POWER CONSUMPTION	8W
EFFICACY	74.25lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B20) 80.000h
COLOUR TEMPERATURE	2700K Ra>80
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	ON-OFF
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	930lm
LUMEN OUTPUT	594lm
EFFICIENCY	63.9%
WEIGHT	3,40 Kg
PROTECTION DEGREE	IP65
COLOUR TOLLERANCES	SDCM 3
SHOCK RESISTANCE RATING	IK06
PACKING DIMENSIONS	27,0 x 35,0 x 22,0 cm



Suspension lighting fixture for indoor or outdoor spaces, with direct light emission. Turned aluminium structure in corten, mat brass or micaceous grey polyacrylic paint.

Transparent silicone gaskets.

Screen in partially mat cast glass.

Aluminium closing disk in polyacrylic paint.

Nickelled brass M12 cable gland.

Stainless steel screws.

3m (118,7") long suspension and power cable in neoprene.

Power canopy with galvanized sheet metal ceiling bracket and die-cast aluminium $\,$ covering in corten, mat brass or micaceous grey polyacrylic paint.











Technical drawing



Polar diagram



<u>cd/klm</u> C0 - C180 - - - C90 - C270