PANZERI

Four

220-240V AC ON-OFF

EP04444.000.0406





Data sheet

CODE	EP04444.000.0406
SYSTEM POWER CONSUMPTION	10W
EFFICACY	59.5lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B50) 60.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	ON-OFF
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	850lm
LUMEN OUTPUT	595lm
EFFICIENCY	70%
WEIGHT	0,69 Kg
PROTECTION DEGREE	IP44
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	19,0 x 19,0 x 14,0 cm



Ceiling or wall lighting fixture for indoor or outdoor spaces, with direct light emission. ${\sf Ceiling/wall\ plate\ in\ die-cast\ aluminium\ in\ metallized\ grey\ polyacrylic\ paint.}$ $\hbox{AISI\,316 stainless steel structure in white or metallized brown polyacrylic paint.}$

EPDM rubber gasket. Aluminium dissipation plate. Flat frosted glass diffuser. Rubber cable grommet. Stainless steel screws.








Technical drawing












Application



Polar diagram



cd/klm C0 - C180 - - - C90 - C270