PANZERI

Bella

220-240V AC ON-OFF L05301.011.0501

Data sheet

| CODE | L05301.011.0501 |
|--------------------------|-----------------------|
| SYSTEM POWER CONSUMPTION | 6,5W |
| EFFICACY | 64.67lm/W |
| LIGHT SOURCE | LED |
| LIGHT SOURCE LIFETIME | L80 (B10) 70.000h |
| COLOUR TEMPERATURE | 2700K Ra>90 |
| LIGHT DISTRIBUTION | diffused |
| POWER SUPPLY | 220-240V AC |
| FREQUENCY | 50/60Hz |
| ELECTRICAL CONFIGURATION | ON-OFF |
| DRIVER | integrated included |
| NOMINAL LUMINOUS FLUX | 460lm |
| LUMEN OUTPUT | 388lm |
| EFFICIENCY | 84.3% |
| WEIGHT | 0,55 Kg |
| PROTECTION DEGREE | IP40 |
| COLOUR TOLLERANCES | SDCM 3 |
| PACKING DIMENSIONS | 13,0 x 24,0 x 12,0 cm |



white

Suspension lighting fixture for interiors, with indirect light emission. Die-cast aluminium structure in white, black, bronze, mat brass or titanium polyacrylic paint.

Modelled acrylic diffuser with mat finish.


Pickled sheet metal closing disk in polyacrylic paint.

Suspension kit with rod in brass tube in polyacrylic paint.

3m (118,1") long suspension and coaxial power cable in transparent PVC.

Power canopy with pickled sheet metal ceiling bracket and extruded aluminium covering in white, black, bronze, mat brass or titanium polyacrylic paint.

Technical drawing



INDIRECT LIGHT