PANZERI

Côte

220-240V AC dimmable (phase cut) L06101.050.0404

white




Data sheet

CODE	L06101.050.0404
SYSTEM POWER CONSUMPTION	22,5W
EFFICACY	85lm/W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (phase cut)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	2702lm
LUMEN OUTPUT	1870lm
EFFICIENCY	69.2%
WEIGHT	4,70 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM <3
PACKING DIMENSIONS	0,0 x 0,0 x 0,0 cm



Technical drawing



Application

black polyacrylic paint.

Suspension lighting fixture for interiors, with direct light emission. Die-cast aluminium structure in black or white polyacrylic paint.

2m (78,7") long steel suspension cables. 2,2m (86,6") long power cable in transparent PVC.

Diffuser screen made of frosted blown glass with matt white or smoke grey finish.

Power canopy with metal ceiling bracket and pickled sheet metal covering in white or