PANZERI

Côte

220-240V AC dimmable (phase cut)

L06102.050.0404





Data sheet

| CODE | L06102.050.0404 |
|--------------------------|----------------------|
| SYSTEM POWER CONSUMPTION | 22,5W |
| EFFICACY | 85lm/W |
| LIGHT SOURCE | LED |
| COLOUR TEMPERATURE | 3000K Ra>90 |
| LIGHT DISTRIBUTION | diffused |
| POWER SUPPLY | 220-240V AC |
| FREQUENCY | 50/60Hz |
| ELECTRICAL CONFIGURATION | dimmable (phase cut) |
| DRIVER | integrated included |
| NOMINAL LUMINOUS FLUX | 2702lm |
| LUMEN OUTPUT | 1870lm |
| EFFICIENCY | 69.2% |
| WEIGHT | 4,70 Kg |
| PROTECTION DEGREE | IP20 |
| COLOUR TOLLERANCES | SDCM <3 |
| PACKING DIMENSIONS | 0,0 x 0,0 x 0,0 cm |
| | |

Suspension lighting fixture for interiors, with direct light emission.

 $\label{thm:continuous} \mbox{ Die-cast aluminium structure in black or white polyacrylic paint.}$

Diffuser screen made of frosted blown glass with matt white or smoke grey finish. 2m (78,7") long steel suspension cables.

2,2m (86,6") long power cable in transparent PVC.


Power canopy with metal ceiling bracket and pickled sheet metal covering in white or black polyacrylic paint.







Technical drawing



Application