PANZERI

Gilbert

220-240V AC ON-OFF


L06501.022.0401





Data sheet

CODE	L06501.022.0401
SYSTEM POWER CONSUMPTION	11W
EFFICACY	84.45lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L90 (B10) 50.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	ON-OFF
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	1157lm
LUMEN OUTPUT	929lm
EFFICIENCY	80.3%
WEIGHT	1,13 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	22,5 x 35,0 x 28,5 cm



Suspension lighting fixture for interiors, with direct and indirect light emission.

Pressed pickled sheet metal structure in white polyacrylic paint. \\

Aluminium dissipation plate.

Diffuser in mat white blown glass.

2m (78,7") long steel suspension cable.

 $2m\,(78,\!7"\!)$ long double power cable in red Teflon.


Power canopy with galvanized sheet metal ceiling bracket and pickled sheet metal $\,$ covering in white polyacrylic paint.








Technical drawing



Polar diagram



<u>cd/klm</u> C0 - C180 - - - C90 - C270