# **PANZERI**

## Kubik

220-240V AC ON-OFF

L07001.011.0401





#### Data sheet

CODE	L07001.011.0401
SYSTEM POWER CONSUMPTION	9,5W
EFFICACY	59.11lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B20) 60.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	ON-OFF
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	861lm
LUMEN OUTPUT	532lm
EFFICIENCY	61.8%
WEIGHT	1,76 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	17,0 x 17,0 x 80,0 cm



Suspension lighting fixture for interiors, with direct and indirect light emission. Pickled sheet metal structure in white polyacrylic paint.

Diffuser in mat white blown glass.

Suspension kit with telescopic rod in brass tube in polyacrylic paint.


Power canopy with galvanized sheet metal ceiling bracket and pickled sheet metal covering in white polyacrylic paint.







#### **Technical drawing**



### Polar diagram

