PANZERI

Golden Ring

220-240V AC dimmable (DALI/Push DIM)

white



Data sheet

2 4 4 4 5 1 5 5 1	
CODE	L08101.080.0402
SYSTEM POWER CONSUMPTION	87W
EFFICACY	70.18lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B20) 80.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	12223lm
LUMEN OUTPUT	6106lm
EFFICIENCY	50%
WEIGHT	10,68 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
GLOW WIRE TEST PERFORMANCE	850°
PACKING DIMENSIONS	90,0 x 25,0 x 90,0 cm



Suspension lighting fixture for interiors, with direct and indirect light emission. Pickled sheet metal structure in polyacrylic paint.

Aluminium dissipation plates.

Aluminium and pickled sheet metal covers in white or black polyacrylic paint, or with gold leaf coating.

Diffusers in modelled polycarbonate with opaline finish.

Suspension kit with griplocks and 2m (78,7") long steel cables.

2,5m (98,4") long power cable in transparent PVC.


Power canopy with galvanized sheet metal ceiling bracket and pickled sheet metal $\,$ covering in white or black polyacrylic paint, or with gold leaf coating.









Technical drawing





Polar diagram



PANZERI

Golden Ring

Accessories / power supply and fixing

M8101-3

Canopy for power supply and to join 3 steel cables.



