

Golden Ring

220-240V AC ON-OFF
L08101.080.0408

white




Data sheet

| | |
|----------------------------|-----------------------|
| CODE | L08101.080.0408 |
| SYSTEM POWER CONSUMPTION | 45W |
| EFFICACY | 67.84lm/W |
| LIGHT SOURCE | LED |
| LIGHT SOURCE LIFETIME | L80 (B20) 80.000h |
| COLOUR TEMPERATURE | 3000K Ra>90 |
| LIGHT DISTRIBUTION | diffused |
| POWER SUPPLY | 220-240V AC |
| FREQUENCY | 50/60Hz |
| ELECTRICAL CONFIGURATION | ON-OFF |
| DRIVER | integrated included |
| NOMINAL LUMINOUS FLUX | 6111lm |
| LUMEN OUTPUT | 3053lm |
| EFFICIENCY | 50% |
| WEIGHT | 9,61 Kg |
| PROTECTION DEGREE | IP40 |
| COLOUR TOLERANCES | SDCM 3 |
| GLOW WIRE TEST PERFORMANCE | 850° |
| PACKING DIMENSIONS | 90,0 x 25,0 x 90,0 cm |




Technical drawing



Suspension lighting fixture for interiors, with direct light emission. Pickled sheet metal structure in polyacrylic paint. Aluminium dissipation plates. Aluminium and pickled sheet metal covers in white or black polyacrylic paint, or with gold leaf coating. Diffuser in modelled polycarbonate with opaline finish. Suspension kit with griplocks and 2m (78,7") long steel cables. 2,5m (98,4") long power cable in transparent PVC. Power canopy with galvanized sheet metal ceiling bracket and pickled sheet metal covering in white or black polyacrylic paint, or with gold leaf coating.

Polar diagram



Golden Ring

Accessories / power supply and fixing

M8101-3

Canopy for power supply and to join 3 steel cables.

