


Silver Ring

220-240V AC dimmable (DALI/Push DIM)
L08221.120.0402




Data sheet

CODE	L08221.120.0402
SYSTEM POWER CONSUMPTION	75W
EFFICACY	69.77lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B20) 80.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	10477lm
LUMEN OUTPUT	5233lm
EFFICIENCY	49.9%
WEIGHT	13,42 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
GLOW WIRE TEST PERFORMANCE	850°
PACKING DIMENSIONS	135,0 x 18,0 x 135,0 cm



Suspension lighting fixture for interiors, with direct light emission.
Pickled sheet metal structure in polyacrylic paint.
Aluminium dissipation plates.
Pickled sheet metal covers in white, black or bronze polyacrylic paint, or with gold leaf coating.
Diffuser in modelled polycarbonate with opaline finish.
Suspension kit with griplocks and 5m (196,9") long steel cables.
5m (196,9") long power cable in transparent PVC.
Power canopy with galvanized sheet metal ceiling bracket and pickled sheet metal covering in white, black or bronze polyacrylic paint, or with gold leaf coating.

Technical drawing



Polar diagram

