PANZERI

Dip

220-240V AC dimmable (DALI/Push DIM)

L08417.000.0502





Data sheet

CODE	L08417.000.0502
SYSTEM POWER CONSUMPTION	18W
EFFICACY	107.28lm/W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	3013lm
LUMEN OUTPUT	1931lm
EFFICIENCY	64.1%
WEIGHT	1,98 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	27,0 x 27,0 x 56,0 cm



Suspension lighting fixture for ceiling installation for interiors, with direct light

Power supply canopy with pickled sheet metal fixing bracket, deep-drawn sheet metal closing frame in polyacrylic paint.

Die-cast aluminum emitting head with polyacrylic paint in champagne, mat black, bronze and soft textured white finishes.

 $\label{eq:continuous} \mbox{UV technology screen-printed diffuser, made of opal polycarbonate, installed with}$

magnetic coupling.


Suspension kit with painted brass tube tige, power supplay and 3m (118.1") long suspension adjustable coaxial cable.








Technical drawing



Polar diagram



<u>cd/klm</u> C0 - C180 - - - C90 - C270

PANZERI

Dip

Accessories / diffusion

YKG08417.01

Anti-glare grid kit for Dip (indoor)



