PANZERI

Ginevra

220-240V AC dimmable (DALI/Push DIM)





Data sheet

| 2010 011001 | |
|--------------------------|--------------------------|
| CODE | L09280.080.0402 |
| SYSTEM POWER CONSUMPTION | 82W |
| EFFICACY | 94.9lm/W |
| LIGHT SOURCE | LED |
| LIGHT SOURCE LIFETIME | L80 (B20) 80.000h |
| COLOUR TEMPERATURE | 3000K Ra>90 |
| LIGHT DISTRIBUTION | diffused |
| POWER SUPPLY | 220-240V AC |
| FREQUENCY | 50/60Hz |
| ELECTRICAL CONFIGURATION | dimmable (DALI/Push DIM) |
| DRIVER | integrated included |
| NOMINAL LUMINOUS FLUX | 10285lm |
| LUMEN OUTPUT | 7782lm |
| EFFICIENCY | 75.7% |
| GLARE RATING | UGR < 19 |
| WEIGHT | 10,97 Kg |
| PROTECTION DEGREE | IP20 |
| COLOUR TOLLERANCES | SDCM <3 |
| PACKING DIMENSIONS | 18,0 x 90,0 x 90,0 cm |
| | |



Suspension lighting fixture for interiors, with direct and indirect light emission. Pickled sheet metal cap in polyacrylic paint.

Turned aluminium structure in mat black and gold or white and gold polyacrylic paint.

Pickled sheet metal wiring support plate in polyacrylic paint.

Moulded polycarbonate micro-prismatic diffuser.

2m (78,7") long steel suspension cables.

2,2m (86,6") long power cable in transparent PVC.


Power canopy with galvanized sheet metal ceiling bracket and pickled sheet metal covering in white or mat black polyacrylic paint.







Technical drawing



Polar diagram

