## PANZERI

### 432 Ways

220-240V AC ON-OFF L12701.006.0501

### Data sheet

CODE	L12701.006.0501
SYSTEM POWER CONSUMPTION	6,7W
EFFICACY	125.5lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L90 (B10) 50.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
BEAM ANGLE	29°
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	ON-OFF
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	858lm
LUMEN OUTPUT	753lm
EFFICIENCY	87.8%
WEIGHT	0,31 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	24,0 x 12,0 x 13,0 cm



Suspension lighting fixture for interiors, with direct light emission. Extruded and milled aluminium structure, with polyacrylic paint finish in white, black, bronze, mat brass, textured olive green or textured natural terracotta. 3m (118,1") long suspension and coaxial power cable in transparent PVC. Power canopy with pickled sheet metal ceiling bracket and extruded aluminium covering with polyacrylic paint.

Lens holder not included, to be purchased separately.

# CE ERE 🗵

### Technical drawing



### Polar diagram

white

Panzeri.it - 23/05/2025 - 432 Ways - L12701.006.0501