

432 Ways

220-240V AC dimmable (DALI/Push DIM)
L12701.010.0402




Data sheet

CODE	L12701.010.0402
SYSTEM POWER CONSUMPTION	16,4W
EFFICACY	119,56lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L90 (B10) 50.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	2077lm
LUMEN OUTPUT	1913lm
EFFICIENCY	92,1%
WEIGHT	0,88 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	24,0 x 12,0 x 13,0 cm



Suspension lighting fixture for interiors, with direct light emission.
Extruded and milled aluminium structure, with polyacrylic paint finish in white, black, bronze, mat brass, textured olive green or textured natural terracotta.
3m (118,1") long suspension and coaxial power cable in transparent PVC.
Power canopy with pickled sheet metal ceiling bracket and extruded aluminium covering with polyacrylic paint.
Lens holder not included, to be purchased separately.

Technical drawing



Polar diagram