


PANZERI

432 Ways

220-240V AC dimmable (DALI/Push DIM)

L12717.006.0502




Data sheet

| | |
|--------------------------|--------------------------|
| CODE | L12717.006.0502 |
| SYSTEM POWER CONSUMPTION | 6,7W |
| EFFICACY | 125.5lm/W |
| LIGHT SOURCE | LED |
| LIGHT SOURCE LIFETIME | L90 (B10) 50.000h |
| COLOUR TEMPERATURE | 2700K Ra>90 |
| LIGHT DISTRIBUTION | diffused |
| BEAM ANGLE | 29° |
| POWER SUPPLY | 220-240V AC |
| FREQUENCY | 50/60Hz |
| ELECTRICAL CONFIGURATION | dimmable (DALI/Push DIM) |
| DRIVER | integrated included |
| NOMINAL LUMINOUS FLUX | 858lm |
| LUMEN OUTPUT | 753lm |
| EFFICIENCY | 87.8% |
| WEIGHT | 0,31 Kg |
| PROTECTION DEGREE | IP20 |
| COLOUR TOLLERANCES | SDCM 3 |
| PACKING DIMENSIONS | 24,0 x 12,0 x 13,0 cm |



Technical drawing



Suspension lighting fixture for interiors, with direct light emission. Extruded and milled aluminium structure, with polyacrylic paint finish in white, black, bronze, mat brass, textured olive green or textured natural terracotta. 3m (118,1") long suspension and coaxial power cable in transparent PVC. Power canopy with pickled sheet metal ceiling bracket and extruded aluminium covering with polyacrylic paint. Lens holder not included, to be purchased separately.

Polar diagram