PANZERI

432 Ways

220-240V AC dimmable (DALI/Push DIM) L12727.006.0402

Data sheet

CODE	L12727.006.0402
SYSTEM POWER CONSUMPTION	6,7W
EFFICACY	128.83lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L90 (B10) 50.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
BEAM ANGLE	29°
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	878lm
LUMEN OUTPUT	773lm
EFFICIENCY	88%
WEIGHT	0,31 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	24,0 x 12,0 x 13,0 cm



textured olive green





Suspension lighting fixture for interiors, with direct light emission. Extruded and milled aluminium structure, with polyacrylic paint finish in white, black, bronze, mat brass, textured olive green or textured natural terracotta. 3m (118,1") long suspension and coaxial power cable in transparent PVC. Power canopy with pickled sheet metal ceiling bracket and extruded aluminium covering with polyacrylic paint. Lens holder not included, to be purchased separately.

CE ERE

Technical drawing



Polar diagram

Panzeri.it - 23/05/2025 - 432 Ways - L12727.006.0402