PANZERI

432 Ways

220-240V AC dimmable (phase cut)

L12727.008.0504





Data sheet

CODE	L12727.008.0504
SYSTEM POWER CONSUMPTION	10,7W
EFFICACY	113.4lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L90 (B10) 50.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (phase cut)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	1328lm
LUMEN OUTPUT	1134lm
EFFICIENCY	85.4%
WEIGHT	0,66 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	24,0 x 12,0 x 13,0 cm



Suspension lighting fixture for interiors, with direct light emission. $\label{thm:extruded} \textbf{Extruded} \ \text{and} \ \textbf{milled} \ \textbf{aluminium} \ \textbf{structure,} \ \textbf{with} \ \textbf{polyacrylic} \ \textbf{paint} \ \textbf{finish} \ \textbf{in} \ \textbf{white,} \ \textbf{black,}$ bronze, mat brass, textured olive green or textured natural terracotta. \\

3m (118,1") long suspension and coaxial power cable in transparent PVC.

Power canopy with pickled sheet metal ceiling bracket and extruded aluminium covering with polyacrylic paint.

Lens holder not included, to be purchased separately.







Technical drawing



Polar diagram