PANZERI

Zero Round Smart


220-240V AC dimmable (ZigBee) L15302.050.0523

Data sheet

| CODE | L15302.050.0523 |
|--------------------------|-----------------------|
| SYSTEM POWER CONSUMPTION | 25W |
| EFFICACY | 81.56lm/W |
| LIGHT SOURCE | LED |
| LIGHT SOURCE LIFETIME | L70 (B50) 60.000h |
| COLOUR TEMPERATURE | 2700K Ra>90 |
| LIGHT DISTRIBUTION | diffused |
| POWER SUPPLY | 220-240V AC |
| FREQUENCY | 50/60Hz |
| ELECTRICAL CONFIGURATION | dimmable (ZigBee) |
| DRIVER | integrated included |
| NOMINAL LUMINOUS FLUX | 2835lm |
| LUMEN OUTPUT | 2039lm |
| EFFICIENCY | 71.9% |
| WEIGHT | 1,91 Kg |
| PROTECTION DEGREE | IP20 |
| COLOUR TOLLERANCES | SDCM 3 |
| PACKING DIMENSIONS | 58,0 x 58,0 x 10,0 cm |



Technical drawing









Suspension lighting fixture for interiors, with direct and indirect light emission. Bended extruded aluminium structure in white, black, bronze, mat brass or titanium polyacrylic paint.

Extruded polycarbonate diffuser with opaline finish. Suspension kit with griplocks and 5m (196,9") long steel cables.

5m (196,9") long power cable in transparent PVC. Power canopy with pickled sheet metal ceiling bracket and covering in white, black,

bronze, mat brass or titanium polyacrylic paint.

Polar diagram

