PANZERI

Brooklyn Round

220-240V AC dimmable (DALI/Push DIM)

white



Data sheet

2 4 4 4 5 1 5 5 1	
CODE	L23201.360.0402
SYSTEM POWER CONSUMPTION	109W
EFFICACY	54.41lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B20) 80.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	13680lm
LUMEN OUTPUT	5931lm
EFFICIENCY	43.4%
WEIGHT	5,78 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
GLOW WIRE TEST PERFORMANCE	850°
PACKING DIMENSIONS	200,0 x 200,0 x 11,0 cm



Suspension lighting fixture for interiors, with direct light emission.

Bended extruded aluminium structure in white, black or mat brass polyacrylic paint.

Extruded polycarbonate diffuser with opaline finish.

Suspension kit with griplocks and 5m (196,9") long steel cables.

5m (196,9") long power cable in transparent PVC.


Power canopy with pickled sheet metal ceiling bracket and covering in white, black or $\,$ mat brass polyacrylic paint.








Technical drawing



Polar diagram



76 ⁵/6"

PANZERI

Brooklyn Round

Accessories / power supply and fixing

XM23101.538.0099

Canopy for power supply with 8 outputs and to join 7 steel cables, for up to 8 Brooklyn Round models maximum.

312





PANZERI

Brooklyn Round

Accessories / fixing

XM231/23201L

Plate for multiple suspensions.



