Bella

24V DC

M05230.011.0510





Data sheet

CODE	M05230.011.0510
SYSTEM POWER CONSUMPTION	4,5W
EFFICACY	97lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B10) 70.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	24V DC
DRIVER	remote not included
NOMINAL LUMINOUS FLUX	460lm
LUMEN OUTPUT	388lm
EFFICIENCY	84.3%
WEIGHT	0,22 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	13,0 x 24,0 x 12,0 cm











Multiple suspension lighting fixture for interiors, with direct light emission. $\label{eq:decomposition} \mbox{Die-cast aluminium structure in white, black, bronze, mat brass or titanium polyacrylic}$ paint.

Modelled acrylic diffuser with mat finish.


Aluminium closing disk in polyacrylic paint.


Suspension kit with rod in brass tube in polyacrylic paint.

3m (118,1") long suspension and coaxial power cable in transparent PVC.


Provided without power canopy, complete with cable clamp on the cable's free extremity.

Technical drawing






Polar diagram




Bella

Accessories / power supply



Bella

Accessories / power supply and fixing



Bella

Accessories / diffusion

YPL05207.015

C € EHI 🗵 🐽

Ivory pleated fabric lampshade, simple snap installation.







