PANZERI

Bella

24V DC M05230.011.0510

Data sheet

CODE	M05230.011.0510
SYSTEM POWER CONSUMPTION	4.5W
EFFICACY	97lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B10) 70.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	24V DC
DRIVER	remote not included
NOMINAL LUMINOUS FLUX	460lm
LUMEN OUTPUT	388lm
EFFICIENCY	84.3%
WEIGHT	0,22 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	13,0 x 24,0 x 12,0 cm

titanium



Multiple suspension lighting fixture for interiors, with direct light emission. Die-cast aluminium structure in white, black, bronze, mat brass or titanium polyacrylic paint.

Modelled acrylic diffuser with mat finish.


Aluminium closing disk in polyacrylic paint.

Suspension kit with rod in brass tube in polyacrylic paint.


3m (118,1") long suspension and coaxial power cable in transparent PVC. Provided without power canopy, complete with cable clamp on the cable's free extremity.

Technical drawing

CEERE 🗵 🐵



Polar diagram



PANZERI

Bella

Accessories / power supply

xm100/24 dim C € ERE X 👜	LED driver, 100W 24V DC, DALI/Push DIM dimmable.	a di la constante di la consta
хм150/24 DIM С Є ЕНЕ 🗵 🐨	LED driver, 150W 24V DC, DALI/Push DIM dimmable.	
хм18/24 DIM С Є ЕПІ 🗵 🐨	LED driver, 18W 24V DC, DALI/Push DIM dimmable.	6 M/r 1/2 mm 0 M/r 1/2 mm
хм35/24 dim С Є ЕНІ 🗵 🔟	LED driver, 35W 24V DC, DALI/Push DIM dimmable.	0 *6*
хм6-20 UNI С Є ЕПП 🗵 🔟	LED driver, 4÷20W 250÷700mA.	R mm 2 ² We
хм60/24 DIM С Є ЕПІ 🗵 💿	LED driver, 60W 24V DC, DALI/Push DIM dimmable.	118 mm 4 2/3* ig
YDV.024.030.A01	LED driver, 30W 24V DC.	2) ≥ 2) ≥ 2) ≥ 2) ≥ 20 ≤ 20 ≤
YDV.024.120.A01	LED driver, 120W 24V DC.	and the second s
YDV.024.180.A01	LED driver, 180W 24V DC.	

PANZERI

Bella

Accessories / diffusion

YPL05207.015



Ivory pleated fabric lampshade, simple snap installation.

