PANZERI

Candle

24V DC

M09501.000.0410





Data sheet


CODE	M09501.000.0410
SYSTEM POWER CONSUMPTION	2,8W
EFFICACY	119lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B50) 60.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	24V DC
DRIVER	remote not included
NOMINAL LUMINOUS FLUX	286lm
LUMEN OUTPUT	238lm
EFFICIENCY	83.2%
WEIGHT	0,37 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	13,0 x 65,0 x 13,0 cm













Turned aluminium heat sink.

Technical drawing



Polar diagram



<u>cd/klm</u> C0 - C180 - - - C90 - C270

Diffuser in partially mat borosilicate glass tube.

³m (118,1") long suspension and power cable in transparent PVC.

Provided without power canopy, complete with cable clamp on the cable's free $\,$ extremity.

PANZERI

Candle

Accessories / power supply

XM100/24 DIM C € [HI] X (m)	LED driver, 100W 24V DC, DALI/Push DIM dimmable.	
XM18/24 DIM C € EHI X (II)	LED driver, 18W 24V DC, DALI/Push DIM dimmable.	
XM35/24 DIM C € EHL (m)	LED driver, 35W 24V DC, DALI/Push DIM dimmable.	
XM6-20 UNI	LED driver, 4÷20W 250÷700mA.	25
XM60/24 DIM C € [EHI] X (m)	LED driver, 60W 24V DC, DALI/Push DIM dimmable.	
YDV.024.030.A01 C € [HI] <u>X</u> (ii)	LED driver, 30W 24V DC.	\$\frac{1}{2} \rightarrow \frac{1}{2} \rightarrow \frac
YDV.024.120.A01	LED driver, 120W 24V DC.	

PANZERI

Candle

Accessories / power supply and fixing

