# **PANZERI**

## Hilow

#### 24V DC

P02817.115.0510





#### Data sheet

CODE	P02817.115.0510
SYSTEM POWER CONSUMPTION	72W
EFFICACY	68.01lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B10) 60.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	24V DC
DRIVER	remote not included
NOMINAL LUMINOUS FLUX	8820lm
LUMEN OUTPUT	4897lm
EFFICIENCY	55.5%
WEIGHT	2,15 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	87,0 x 118,0 x 14,0 cm



Ceiling lighting fixture for interiors, with direct and indirect light emission.

Pickled sheet metal ceiling bracket in polyacrylic paint.

Pickled sheet metal wall plate in polyacrylic paint.

Extruded aluminium structure in white, mat black, bronze, mat brass or titanium polyacrylic paint.

Joints in turned brass and die-cast aluminium in polyacrylic paint.

Die-cast aluminium end caps in polyacrylic paint.

Extruded polycarbonate diffusers with opaline finish.











#### Technical drawing





### Polar diagram



<u>cd/klm</u> C0 - C180 - - - C90 - C270

# **PANZERI**

# Hilow

### Accessories / power supply

