PANZERI

One

220-240V AC dimmable (DALI/Push DIM)

P03701.000.0402





Data sheet

CODE	P03701.000.0402
SYSTEM POWER CONSUMPTION	15W
EFFICACY	68.13lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L90 (B10) 50.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	1611lm
LUMEN OUTPUT	1022lm
EFFICIENCY	63.4%
WEIGHT	0,77 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	23,0 x 31,0 x 13,0 cm



Ceiling lighting fixture for interiors, with direct light emission.

 $\label{thm:continuous} \text{Turned pickled sheet metal ceiling bracket in white, black, bronze, mat brass or gold}$ polyacrylic paint.

 $\label{prop:eq:extruded} \textbf{Extruded aluminium structure in white, black, bronze or mat brass polyacrylic paint, or }$ with gold leaf coating.

Aluminium dissipation plate.

Flat frosted glass diffuser.


Turned pickled sheet metal frame in white, black, bronze or mat brass polyacrylic paint, or with gold leaf coating.








Technical drawing



Polar diagram



<u>cd/klm</u> C0 - C180 - - - C90 - C270