# **PANZERI**

## One

220-240V AC ON-OFF

P03721.000.0401





#### Data sheet

CODE	P03721.000.0401
SYSTEM POWER CONSUMPTION	15W
EFFICACY	68.13lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L90 (B10) 50.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	ON-OFF
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	1611lm
LUMEN OUTPUT	1022lm
EFFICIENCY	63.4%
WEIGHT	0,77 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	23,0 x 31,0 x 13,0 cm



Ceiling lighting fixture for interiors, with direct light emission.

 $\label{thm:continuous} \text{Turned pickled sheet metal ceiling bracket in white, black, bronze, mat brass or gold}$ polyacrylic paint.

 $\label{prop:eq:extruded} \textbf{Extruded aluminium structure in white, black, bronze or mat brass polyacrylic paint, or }$ with gold leaf coating.

Aluminium dissipation plate.

Flat frosted glass diffuser.


Turned pickled sheet metal frame in white, black, bronze or mat brass polyacrylic paint, or with gold leaf coating.








### **Technical drawing**



## Polar diagram



<u>cd/klm</u> C0 - C180 - - - C90 - C270