# **PANZERI**

### Three

220-240V AC ON-OFF


P03901.015.0406





#### Data sheet

| CODE                     | P03901.015.0406       |
|--------------------------|-----------------------|
| SYSTEM POWER CONSUMPTION | 15W                   |
| EFFICACY                 | 63.73lm/W             |
| LIGHT SOURCE             | LED                   |
| LIGHT SOURCE LIFETIME    | L70 (B50) 50.000h     |
| COLOUR TEMPERATURE       | 3000K Ra>90           |
| LIGHT DISTRIBUTION       | diffused              |
| POWER SUPPLY             | 220-240V AC           |
| FREQUENCY                | 50/60Hz               |
| ELECTRICAL CONFIGURATION | ON-OFF                |
| DRIVER                   | integrated included   |
| NOMINAL LUMINOUS FLUX    | 1275lm                |
| LUMEN OUTPUT             | 956lm                 |
| EFFICIENCY               | 75%                   |
| WEIGHT                   | 1,32 Kg               |
| PROTECTION DEGREE        | IP40                  |
| COLOUR TOLLERANCES       | SDCM 3                |
| PACKING DIMENSIONS       | 20,0 x 20,0 x 22,0 cm |
|                          |                       |



Ceiling or wall lighting fixture for interiors, with direct light emission.

Pickled sheet metal ceiling/wall bracket in polyacrylic paint.

 $\label{prop:extruded} \textbf{Extruded aluminium structure in white, black, bronze or mat brass polyacrylic paint.}$ Aluminium dissipation plate.

Flat frosted glass diffuser.


Pickled sheet metal frame in polyacrylic paint.








### Technical drawing






### **Application**



#### Polar diagram



cd/klm C0 - C180 - - - C90 - C270

# **PANZERI**

## Three

### Accessories / dimming

XM14/230

Dimmable device for 230V LED modules, 5÷100W.



