

PANZERI

Three

220-240V AC ON-OFF
P03917.011.0406




Data sheet

CODE	P03917.011.0406
SYSTEM POWER CONSUMPTION	10W
EFFICACY	59.5lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B50) 50.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	ON-OFF
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	850lm
LUMEN OUTPUT	595lm
EFFICIENCY	70%
WEIGHT	0,51 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	12,0 x 24,0 x 13,0 cm



Ceiling or wall lighting fixture for interiors, with direct light emission.
Pickled sheet metal ceiling/wall bracket in polyacrylic paint.
Extruded aluminium structure in white, black, bronze or mat brass polyacrylic paint.
Aluminium dissipation plate.
Flat frosted glass diffuser.
Pickled sheet metal frame in polyacrylic paint.


Technical drawing



Application



Polar diagram



PANZERI

Three

Accessories / dimming

XM14/230

Dimmable device for 230V LED modules, 5÷100W.

