# **PANZERI**

# Côte

220-240V AC dimmable (phase cut)

P06001.035.0504

## white



#### Data sheet

CODE	P06001.035.0504
SYSTEM POWER CONSUMPTION	19W
EFFICACY	78.16lm/W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (phase cut)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	2312lm
LUMEN OUTPUT	1485lm
EFFICIENCY	64.2%
WEIGHT	3,40 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM <3
PACKING DIMENSIONS	0,0 x 0,0 x 0,0 cm



Ceiling or wall lighting fixture for interiors, with direct light emission.  $\label{thm:continuous} \mbox{ Die-cast aluminium structure in white polyacrylic paint.}$ 


Diffuser screen made of frosted blown glass with matt white or smoke grey finish. Pickled sheet metal covering with ceiling fixing bracket in white polyacrylic paint.







### Technical drawing



## **Application**

