PANZERI

Gilbert

220-240V AC dimmable (DALI/Push DIM)

P06501.045.0402

white



Data sheet

CODE	P06501.045.0402
SYSTEM POWER CONSUMPTION	20W
EFFICACY	92lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L90 (B10) 50.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	2301lm
LUMEN OUTPUT	1840lm
EFFICIENCY	80%
WEIGHT	5,12 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	0,0 x 0,0 x 0,0 cm



Ceiling lighting fixture for interiors, with direct and indirect light emission. Galvanized sheet metal ceiling bracket.

Turned pickled sheet metal structure in white polyacrylic paint.

 $Wall\ plate\ with\ lever-closing\ mechanism\ in\ pressed\ pickled\ sheet\ metal\ in\ white\ powder$

Extruded aluminium heat sink.


Diffuser in mat white blown glass.








Technical drawing



Polar diagram



<u>cd/klm</u> C0 - C180 - - - C90 - C270