# **PANZERI**

## Jackie

220-240V AC ON-OFF

P07730.000.0101





#### Data sheet

| 2010 0.1001              |                       |
|--------------------------|-----------------------|
| CODE                     | P07730.000.0101       |
| SYSTEM POWER CONSUMPTION | 8,5W                  |
| EFFICACY                 | 102.5lm/W             |
| LIGHT SOURCE             | LED                   |
| LIGHT SOURCE LIFETIME    | L90 (B10) 50.000h     |
| COLOUR TEMPERATURE       | 3000K Ra>80           |
| LIGHT DISTRIBUTION       | adjustable            |
| BEAM ANGLE               | 90°                   |
| POWER SUPPLY             | 220-240V AC           |
| FREQUENCY                | 50/60Hz               |
| ELECTRICAL CONFIGURATION | ON-OFF                |
| DRIVER                   | integrated included   |
| NOMINAL LUMINOUS FLUX    | 1027lm                |
| LUMEN OUTPUT             | 820lm                 |
| EFFICIENCY               | 79.8%                 |
| WEIGHT                   | 0,46 Kg               |
| PROTECTION DEGREE        | IP40                  |
| COLOUR TOLLERANCES       | SDCM 3                |
| PACKING DIMENSIONS       | 12,0 x 24,0 x 13,0 cm |
|                          |                       |



Ceiling or wall lighting fixture for interiors, with swivelling light beam. Pickled sheet metal ceiling/wall bracket in polyacrylic paint.

Die-cast aluminium wall plate in polyacrylic paint.

 $\label{thm:continuous} \mbox{Die-cast aluminium structure in white, black, red or titanium polyacrylic paint.}$ 

Die-cast aluminium head rotating on two axes in polyacrylic paint.


 $\label{thm:modelled} \mbox{Modelled acrylic diffuser with mat finish and double serigraphy}.$ 







### Technical drawing






### **Application**



#### Polar diagram



cd/klm C0 - C180 - - - C90 - C270