# **PANZERI**

## Silver Ring

220-240V AC dimmable (DALI/Push DIM)

P08201.080.0402





#### Data sheet

CODE	P08201.080.0402
SYSTEM POWER CONSUMPTION	45W
EFFICACY	67.84lm/W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	6111lm
LUMEN OUTPUT	3053lm
EFFICIENCY	50%
WEIGHT	7,63 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
GLOW WIRE TEST PERFORMANCE	850°
PACKING DIMENSIONS	90,0 x 18,0 x 90,0 cm



Ceiling or wall lighting fixture for interiors, with direct light emission.

Pickled sheet metal ceiling/wall bracket in polyacrylic paint.

Pickled sheet metal structure in polyacrylic paint.

Aluminium dissipation plates.

Pickled sheet metal covers in white, black or bronze polyacrylic paint, or with gold leaf

 $\label{thm:modelled} \mbox{Modelled polycarbonate diffuser with opaline finish.}$ 









#### Technical drawing








### **Application**



#### Polar diagram



cd/klm C0 - C180 - - - C90 - C270