# **PANZERI**

# Silver Ring

220-240V AC dimmable (DALI/Push DIM)

P08201.120.0402

### white



#### Data sheet

CODE	P08201.120.0402
SYSTEM POWER CONSUMPTION	75W
EFFICACY	69.77lm/W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	10477lm
LUMEN OUTPUT	5233lm
EFFICIENCY	49.9%
WEIGHT	11,63 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
GLOW WIRE TEST PERFORMANCE	850°
PACKING DIMENSIONS	135,0 x 18,0 x 135,0 cm
-	



Ceiling or wall lighting fixture for interiors, with direct light emission.

Pickled sheet metal ceiling/wall bracket in polyacrylic paint.

Pickled sheet metal structure in polyacrylic paint.

Aluminium dissipation plates.

Pickled sheet metal covers in white, black or bronze polyacrylic paint, or with gold leaf


 $\label{thm:modelled} \mbox{Modelled polycarbonate diffuser with opaline finish.}$ 







## Technical drawing



### **Application**



#### Polar diagram

